

SLOTOCLEAN DS 10 Nitric - Free Desmut

SLOTOCLEAN DS 10 Nitric-Free Desmut is a new generation process for the pre-treatment of aluminium prior to electroless or electrolytic plating.

SLOTOCLEAN DS 10 Nitric-Free Desmut is used for the removal of smut formed during the chemical etching of aluminium.

SLOTOCLEAN DS 10 Nitric-Free Desmut is especially suited for the processing of wrought aluminium alloys, it is also suitable for use on some cast alloys.

SLOTOCLEAN DS 10 Nitric-Free Desmut:

- has a long life.
- is easily maintained.
- has negligible attack on the substrate.
- is easy to waste treat.
- is a viable alternative to nitric acid.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important :

Please read these instructions carefully and follow recommendations given.

We reserve the right to make technical changes as necessary.

In the interests of safety, please pay attention to the R- and S- phrases on the drum label.

The shelf life of the additives is generally 18 months.

The date of production is taken from the first 3 figures of the batch number.

Figure 1 = year; figures 2-3 = month; figures 4-7 = batch number; (UK labels use a 4 digit year code).

For the storage of chemical products only the Hazardous Substances Regulation must be followed.

The Hazardous Goods Regulation (ADR/GGVS) are only valid for transportation and must not be applied to storage.