

Conservation SLOTOPROTECT FE 1050

Conservation SLOTOPROTECT FE 1050 is being applied in an immersion process and is a temporary corrosion protection to prevent from film rust on ferrous materials. The possible fields of application are:

- Temporary storage of degreased parts prior to further processing.
- Prevention from internal corrosion at hollow ware, chromate in a trivalent chrome electrolyte.
- Prevention from internal corrosion at zinc-nickel coated hollow ware.

The parts treated in Conservation SLOTOPROTECT FE 1050 normally dry off spot-free. The product has no interfering influence on subsequent processes like e.g. powder coating or lacquering.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance only. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instruction carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

