

Neutraliser PT 10

Neutraliser PT 10 is a weakly alkaline (pH value approx. 8 - 9) post-treatment for tinned or with lead-tin coated components. The make-up is performed with a liquid concentrate.

Neutraliser PT 10 effectively removes processing residues from the surface of the plated components and enhances at the same time long term solderability.

Neutraliser PT 10 has been developed for application at low operating temperatures. But the application over a wide temperature range is possible. Neutraliser PT 10 is non-foaming and can be used in both barrel- and rack applications as well as in reel-to-reel plating lines.

Neutraliser PT 10 is free from AOX.

The information in this data sheet is based on laboratory as well as practical experience. Figures quoted for operating limits and replenishment quantities are for guidance only. Actual values necessary will depend on the components being plated (material and geometry), their application and plating plant conditions.

Important:

Please read this instructions carefully prior to the use of the process and carefully follow all the parameters that have a direct influence on the operation. We reserve the right to make technical changes. In the interest of safety, please pay attention to the hazard warnings on the labels of the containers. The minimum shelf life of the products is included on the labels and is also available in the appropriate Quality Assurance (QA03).

The current IMDS number of the layer deposited from the process is available on the internet at www.schloetter.com/downloads.

For the storage of chemical products the TRGS 510 must be followed.

If the additives used in this process contain a SVHC-substance, then this will be specified in the corresponding Material Safety Data Sheet, section 15.

